

PURGING / CLEANING COMPOUND MASTERBATCHES

NASSOLKEM KlariFos™ Purging / Cleaning Compound MasterBatches

True Universal Color-n-Additive MasterBatches



PRODUCT INFORMATION

PURGING / CLEANING COMPOUND MASTERBATCHES

NASSOLKEM KlariFos™ Purging / Cleaning Compound MasterBatches

KlariFos™ cleaning & purging compound MasterBatch removes plastic-n-color residue from mold & dies. It also helps to remove the remains of residue caused by Polymer & Additive degradation. It provides time saving production process, molding with flawless surface structure and fast change of colors.

Ideal cleaner for Injection molding machines, Blow molding machines, Extruders & also useful in hot runner molds.

KlariFos™ ensures fast & efficient purging which results in minimum material wastage.

Salient Features:

- a) Suitable for purging needs for processing temperature up to 320°C.
- b) No odour during application.
- c) Suitable for use in all application including use in hot runner molds.
- d) Contains no abrasives.
- e) Completely removes polymer & additive residue including color, wax, oil etc. Also removes burnt deposits.
- f) Rapid cleaning effect, also suitable for mold cleaning & degreasing.
- g) Can be used in overnight & weekend shutdowns.
- h) True Universal compatibility in plastics & rubber.





PROCEDURE & Instructions for use in Injection / Blow molding machines.


- a) Eject the inside polymer completely.
- b) Carefully clean the hopper when dry colors are used.
- c) Add **KlariFos™** alone only into hopper.
- d) Continue the normal procedure of molding till it flushes out all polymer-n- color residues.
- e) Eject **KlariFos™** completely & start with your next production with no change in required color & no loss of material.

KlariFos™ can be effectively used in shutdown of machines for Holidays or for longer time if production is stopped for some days. The procedure is same as above with only change being to leave **KlariFos™** in the cylinder & switch off the machine. Due to much longer time available to **KlariFos™**, it will result in better cleaning performance when restarted.

Dosage : 2 Kg to 10 Kg required as per the size of machine & polymer/ color residue deposits.

Shelf life : Long Life

Note: This information is solely for your consideration, investigation & verification. It is not to be taken as a warranty or representation.



NASSOLKEM (P) LTD.
BULBUL MASTERBATCHES (P) LTD.

Manufacturing Sites in India:
Athal, Piparia (Silvassa), Pune, Sachin & Pandesara.

Export Office:

209, Hari Chamber,
58/64, Shahid Bhagat Singh Road,
Fort, Mumbai - 400 001 (INDIA).
Tel : +91-22-22702811/12
Fax : +91-22-22702810
Email : export@nassolkem.in
export@bulbul.in
Web : www.nassolkem.in
www.bulbul.in

Head Office :

Gurukrupa, Ground Floor,
133, Kazi Sayed Street,
Mumbai - 400 003. (INDIA).
Tel : +91-22-23412811/12
Fax : +91-22-23433810
Email : sales@nassolkem.in
sales@bulbul.in
Web : www.nassolkem.in
www.bulbul.in